

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 603 301 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
07.12.2005 Bulletin 2005/49

(51) Int Cl.7: **H04L 29/06, G06F 17/60**

(21) Application number: **05017557.9**

(22) Date of filing: **06.05.2003**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR**
Designated Extension States:
AL LT LV MK

(72) Inventors:
• **Lau, Anthony P.**
Kitchener Ontario, N2C 2J9 (CA)
• **Curelet-Balan, Gheorghe**
Kitchener Ontario, N2C 2C (CA)

(30) Priority: **06.05.2002 US 377644 P**

(74) Representative: **Hibbert, Juliet Jane Grace et al**
Kilburn & Strode,
20 Red Lion Street
London WC1R 4PJ (GB)

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
03252820.0 / 1 361 727

Remarks:
This application was filed on 12 - 08 - 2005 as a
divisional application to the application mentioned
under INID code 62.

(71) Applicant: **Research in Motion**
Waterloo, Ontario N2L 3W8 (CA)

(54) **Event reminder method**

(57) A mobile device that uses events as triggers for reminders in addition to date and time. Such events may be location-based, or based on other events or tasks scheduled by the user and other events or tasks scheduled by another user.

EP 1 603 301 A1

Description

[0001] This application incorporates by reference and claims the benefit of priority from U.S. Provisional Application No. 60/377,644 filed on May 6, 2003.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] This invention relates to the field of notification applications. In particular this invention relates to an event reminder method for mobile devices.

Description of the State of the Art

[0003] A mobile device includes a two-way communication device, a data-messaging device, a two-way pager, a cellular telephone with data messaging capabilities, a wireless Internet appliance, and a data communication device. The mobile device includes a micro-processor that controls at least a display, flash memory, RAM, auxiliary input/output (I/O) subsystems, serial port, a keyboard, and a short-range communications subsystem.

[0004] Most scheduling applications on mobile devices use dates and times for scheduling. For example, a calendar application may signal an alert to remind a user of an upcoming appointment a set amount of time before the appointment starts. Typical calendar applications do not take into account delays, how long tasks take to accomplish, sequence of events, or another user's task list or location.

SUMMARY

[0005] In one aspect of the invention, there is provided an application for a mobile device that uses events as triggers for reminders in addition to date and time. Such events may be location-based, or based on other events or tasks scheduled by the user and other events or tasks scheduled by another user.

[0006] In another aspect of the invention, there is provided a mobile device that uses events as triggers for reminders in addition to date and time. Such events may be location-based, or based on other events or tasks scheduled by the user and other events or tasks scheduled by another user.

[0007] Further features of the invention will be described or will become apparent in the course of the following detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] In order that the invention may be more clearly understood, the one or more embodiments thereof will now be described in detail by way of example, with reference to the accompanying drawings, in which:

Fig. 1 is a block diagram displaying the different types of reminders for a handheld device;

Fig. 2 is a flow diagram showing the steps taken when a user creates a reminder for an event on a handheld device;

Fig. 3 is a flow diagram showing more detailed steps when a user creates a reminder for an event based on second user's task list;

Fig. 4 is a flow diagram showing the steps for a first user's device to request location updates from a second user's device;

Fig. 5 is a flow diagram showing steps for a first user to send location updates to one or more other users; and

Fig. 6 is a schematic diagram of a wireless communication device that may be used with the systems and methods described herein.

DETAILED DESCRIPTION

[0009] Fig. 1 is a block diagram displaying the structure of an event, either from a task list application or a calendar application on a handheld device. An event 50 is comprised preferably of text 52, status 54, priority 56, and a deadline 58. Text 52 may include the subject or title of the event 50. Status 54 is preferably defined by the state of the progress of the event 50. For example, if the event 50 hasn't begun yet, then the status 54 may be set to 'Not Started'. If the event 50 has been started and not completed, the status 54 preferably is set to 'In Progress'. If the event 50 has been finished, then the status 54 changes to 'Completed'. These are illustrative examples of the status 54 of an event 50 and are not limited to these examples. A plurality of examples and possible states may exist.

[0010] The priority 56 of an event 50 is defined preferably as the importance of the event 50 and may be set to low, normal or high. This setting is based on the urgency of the event 50.

[0011] The deadline 58 of an event 50 is defined preferably as the limiting factor of the event. The event 50 is completed whenever the deadline 58 requirements are satisfied. When the deadline 58 is set, a reminder 60 may be set to remind a user of the deadline 58. The reminder 60 may be set according to at least one preference such as time 62, location 66, a personal task 70 from the device task list application, an event from second user's device task list application or calendar 74, or a second user's location 78. The reminders are not limited to these exemplary preferences, and may be set according to a plurality of preferences.

[0012] The preferable default preference for a reminder 60 is time 62. If the user chooses to base the reminder 60 on time 62, the user chooses a date or time for which the reminder 60 is to be triggered.

[0013] If the user chooses to trigger the reminder 60 with a location 66, the user preferably sets the location for which the reminder is to activate. The location may

be listed as a base station of GPS (Global Position System) coordinate. When the user enters said location. Location may be defined in several ways, not limited to, but including base station identifiers, latitude/longitude coordinates, and geographical mapping information (such as area names of cities, regions, countries, etc.). It will be understood by those skilled in the art that the location may be detected from a number of different location detection means, which means include GPS, proximity to a beacon, and proximity to a base-station.

[0014] In terms of the display of location information to the user, the technical methods that the device may use to determine location may not need to be shown in its entirety. Abstraction of this information is possible through the use of device-based software, computer-based software connected to the device, and or waypoint information (as a user defined location). Using additional location-based software tools, the user may be able to choose from a database of locations pre-programmed into the software. The user may then choose from this list, leaving the technical determination to the software. Similarly, software may also be used to help define customizable areas (for example, via mouse input on a computer), which may then be used to build a database for the user to select as described above. Waypoints are another method of entry whereby the user may easily enter in an area by using current location as a marker. At a particular location that the user wishes to mark and record for future use, the user may save the user's present location to a database on the device. Subsequently, the user may then use this waypoint as criteria for future reminders.

[0015] The user may choose to base an event reminder 60 on a task from the user's device's task list application 70. In this case, once a task is marked as complete, preferably the reminder 60 for the second task is triggered 72. To set the reminder, the device preferably lists the uncompleted tasks for the user to choose from.

[0016] If a first user chooses to base a first event reminder 60 on a second event from a second user's device's task list application or calendar application 74, the first device preferably seeks permission from the second user in order to link the two events. If permission is granted by the second user, then whenever the second user marks the chosen second event as completed, the second user's device notifies the first user's device, triggering the reminder for the first event. Further alternately, the second user's device may notify the first user's device using email notification where the second user's device notifies the first user's device with an email having the reminder for the first event (where the second user's device having been provided with the reminder for the first event as part of the seeking permission).

[0017] The user may choose to base an event reminder 60 on a second user's location 78. The first device preferably requests updates of a second user. The second user's device either pushes the location updates to the first user's device or the first user's device polls the

second user's device for the updates.

[0018] In a further embodiment the user may be able to choose an event reminder based on combinations of preferences. For example, the user may choose to base event reminders on a series of tasks as well as time. In this case, when a user creates a series of tasks, a reminder for a first task may be set according to an elapsed amount of time from when the task started. A reminder for a second task may depend on both the relative time from when the first task was completed.

[0019] Fig. 2 is a flow diagram showing the steps taken when a user creates a reminder on a handheld device. When a user creates a task or a calendar event, the user may be able to set a reminder for the task or appointment as an option in step 80. The reminder is preferably based on several factors that the user may choose from. If the user decides to base the reminder on location in step 82, then the user chooses a location for which the reminder notifies the user of the task or appointment in step 84. In step 86, the device detects when the user has entered the chosen location and in step 88, the device notifies or remind the user of the task or appointment.

[0020] If the reminder is not based on location, then a reminder may be based on the completion of a first task in step 90. In step 92, the user preferably chooses a task from the task list on the device. This first task is marked for completion before the reminder notifies the user of a second task. In step 94, when the user completes the first task and marks the first task in the task list as completed, then the device reminds the user of the impending appointment or next task in step 88. An example of when such a reminder may be used is in the form of a recipe. A user may enter the series of steps of the recipe as tasks. For a recipe with sequential steps, the user may set a reminder for a second step of a recipe based on the completion of a first step of the recipe that immediately preceded the second step.

[0021] If the reminder is not based on either location or the completion of a first task, then the reminder may be based on the completion of second user's event as in step 96. When a reminder is based on completion of an event in second user's task list or calendar, then when that other person has marked the chosen event for completion, preferably an update is sent from the other person's device or organizer to the user's device in step 98. Then the device preferably reminds the user of the impending appointment or task that was saved on the device in step 88.

[0022] If the reminder is not based on any of the above, then the reminder is based preferably on a default of time or date. In step 100, the user preferably chooses a date or time that the user wishes to be reminded of the appointment or task that the user has created. In step 102, once this date or time has occurred, the device preferably alerts the user to remind the user of the impending event that needs to be completed in step 88.

[0023] Fig. 3 is a flow diagram showing more detailed steps when a user creates a reminder based on second user's event. A first user chooses to base the reminder on the completion of a second user's event in step 110. The first user chooses the second user. Preferably, this selection is made from the first user's contact list or address book application on the device. This selection may also be made from an e-mail address that the first user enters.

[0024] Once the second user is selected, preferably, a request from the first user's device is sent to the second user requesting to link the first user's event to an event in the second user's task list or calendar in step 114. If, in step 116, the second user does not accept the first user's request, then in step 118, the second user's device preferably sends a rejection to the first user.

[0025] If the second user accepts the first user's request, then in step 120, preferably the second user's device opens the task list or calendar from which the second user chooses the event to be linked to the first user's event. Once this second event is chosen by the second user, the second user's device preferably sends a response to the first user detailing the second event of the second user to which the first user's event is linked.

[0026] Fig. 4 is a flow diagram showing the steps for a first user to request location information from a second user. In step 126, the first user creates an event with a reminder for updates of a second user's location. The first user chooses a second user, in step 128. The first user preferably chooses the second user from an address list application on the device. In step 130, the first user's device sends a request to the second user for updates on the second user's location. If in step 132, the second user does not accept the first user's request, in step 134, a rejection of the first user's request is sent from the second user's device to the first user's device.

[0027] If in step 132, the second user accepts the first user's request, then in step 136, the second user's device sends an acceptance response to the first user.

[0028] The location information may be either pushed or pulled from the second user's device. If in step 138, the information is pushed to the first user's device from the second user's device, then in step 140, the second user's device preferably detects its location through mechanisms such as GPS, base station identification, or via geographical mapping software on the device or on a server at regular intervals. In step 142, the second user's device preferably sends the detected location to the first user's device.

[0029] If in step 138, the information is not pushed to the first user's device, then in step 144, the first user's device preferably polls the second user's device for an update of the second user's location. In step 146, upon receiving the query from the first user's device, the second user's device preferably detects its location. The second user's device preferably sends the location that was detected to the first user's device.

[0030] Fig. 5 is a flow diagram showing the steps for

updating a user's location. In step 150, a first user creates a reminder to update one or more other users of the first user's location. In step 152, the first user sends the reminder to the one or more other users. An example of this may be when a mail delivery person progress along his/her route, wishing to update his/her current location to the post office. The device then starts updating people of the location, either on a periodic basis or when polled by the other users. The first user's location information may be pushed to the one or more other users or the one or more other users may request the first user's location information from the user's device, as depicted in step 154.

[0031] If the location information is pushed to the one or more other users, then the first user's device preferably detects the location through mechanisms such as GPS, base station identification, detecting whether the device is in or out of a docking cradle, or via geographical mapping software on the device or on a server, in step 156. In step 158, the first user's device preferably sends the location information to the one or more other users.

[0032] If the location information is requested by the one or more other users, then in step 160, the one or more other users preferably poll the first user's device for the location information. In step 142, the first user's device preferably detects the information when it receives the request from the one or more other users. The first user's device preferably sends the location information to the one or more other users, as in step 158.

[0033] Fig. 6 shows a typical mobile communication device 610, which is preferably a two-way communication device. The device preferably has the capability to communicate with other computer systems on the Internet. Depending on the functionality provided by the device, the device may be referred to as a data messaging device, a two-way pager, a cellular telephone with data messaging capabilities, a wireless Internet appliance or a data communication device (with or without telephony capabilities).

[0034] Where the device 610 is enabled for two-way communications, the device incorporates a communication subsystem 611, including a receiver 612, a transmitter 614, and associated components such as one or more, preferably embedded or internal, antenna elements 616 and 618, local oscillators (LOs) 613, and a processing module such as a digital signal processor (DSP) 620. As will be apparent to those skilled in the field of communications, the particular design of the communication subsystem 611 is dependent upon the communication network in which the device is intended to operate. For example, a mobile device 610 destined for a North American market may include a communication subsystem 611 designed to operate within the Mobitex mobile communication system or DataTAC mobile communication system, whereas a mobile device 610 intended for use in Europe may incorporate a GPRS communication subsystem 611.

[0035] Network access requirements also vary de-

pending upon the type of network 619. For example, in the Mobitex and DataTAC networks, mobile devices such as 610 are registered on the network using a unique identification number associated with each device. In GPRS networks however, network access is associated with a subscriber or user of a device 610. A GPRS device therefore requires a subscriber identity module (not shown), commonly referred to as a SIM card, in order to operate on a GPRS network. Without a SIM card, a GPRS device will not be fully functional. Local or non-network communication functions (if any) may be operable, but the mobile device 610 will be unable to carry out any functions involving communications over network 619.

[0036] When required network registration or activation procedures have been completed, a mobile device 610 may send and receive communication signals over the network 619. Signals received by the antenna 616 through a communication network 619 are input to the receiver 612, which may perform such common receiver functions as signal amplification, frequency down conversion, filtering, channel selection and the like, and in the example system shown in Fig. 6, analog to digital conversion. Analog to digital conversion of a received signal allows more complex communication functions such as demodulation and decoding to be performed in the DSP 620. In a similar manner, signals to be transmitted are processed, including modulation and encoding for example, by the DSP 620 and input to the transmitter 614 for digital to analog conversion, frequency up conversion, filtering, amplification and transmission over the communication network 619 via the antenna 618.

[0037] The DSP 620 not only processes communication signals, but also provides for receiver and transmitter control. For example, the gains applied to communication signals in the receiver 612 and transmitter 614 may be adaptively controlled through automatic gain control algorithms implemented in the DSP 620.

[0038] The mobile device 610 preferably includes a microprocessor 638 that controls the overall operation of the device. Communication functions, including at least data and voice communications, are performed through the communication subsystem 611. The microprocessor 638 also interacts with further device subsystems such as the display 622, flash memory 624, RAM 626, auxiliary input/output (I/O) subsystems 628, serial port 630, keyboard 632, speaker 634, microphone 636, a short-range communications subsystem 640 and any other device subsystems generally designated as 642.

[0039] Within the Flash memory 624, the device 610 preferably includes a plurality of software modules 624A-624N that are executed by the microprocessor 638 (and/or the DSP 620), including a voice communication module 624A, a data communication module 624B, a calendar software module 624C, a task list software module 624D, and a plurality of other operational modules 624N for carrying out a plurality of other func-

tions.

[0040] Some of the subsystems shown in Fig. 6 perform communication-related functions, whereas other subsystems may provide "resident" or on-device functions. Notably, some subsystems, such as keyboard 632 and display 622 for example, may be used for both communication-related functions, such as entering a text message for transmission over a communication network, and device-resident functions such as a calculator or task list.

[0041] Operating system software used by the microprocessor 638 is preferably stored in a persistent store such as Flash memory 624. In addition to the operating system, which controls all of the low-level functions of the device 610, the Flash memory 624 may include a plurality of high-level software application programs, or modules, such as a voice communication module 624A, a data communication module 624B, a calendar module 624C, a task list module 624D, or any other type of software module 624N. The Flash memory 624 also may include a file system for storing data. These modules are executed by the microprocessor 638 and provide a high-level interface between a user of the device and the device. This interface typically includes a graphical component provided through the display 622, and an input/output component provided through the auxiliary I/O 628, and keyboard 632. If the device includes a voice communications module then a speaker 634, and microphone 636 may also be included. The operating system, specific device applications or modules, or parts thereof, may be temporarily loaded into a volatile store, such as RAM 626 for faster operation. Moreover, received communication signals may also be temporarily stored to RAM 626, before permanently writing them to a file system located in the persistent store 624.

[0042] Further application modules 624N may also be loaded onto the mobile device 610 through the network 619, an auxiliary I/O subsystem 628, serial port 630, short-range communications subsystem 640 or any other suitable subsystem 642, and installed by a user in the RAM 626 or preferably a non-volatile store for execution by the microprocessor 638. Such flexibility in application installation increases the functionality of the device and may provide enhanced on-device functions, communication-related functions, or both. For example, secure communication applications may enable electronic commerce functions and other such financial transactions to be performed using the mobile device 610.

[0043] In a data communication mode, a received signal such as a text message or web page download is processed by the communication subsystem 611 and input to the microprocessor 638, which is preferably further process the received signal for output to the display 622, or alternatively to an auxiliary I/O device 628. A user of mobile device 610 may also compose data items such as email messages for example, using the keyboard 632, which is preferably a complete alphanumeric keyboard or telephone-type keypad, in conjunction with

the display 622 and possibly an auxiliary I/O device 628. Such composed items may then be transmitted over a communication network through the communication subsystem 611.

[0044] For voice communications, overall operation of the mobile device 610 is substantially similar, except that received signals are preferably outputs to a speaker 634 and signals for transmission are generated by a microphone 636. Alternative voice or audio I/O subsystems such as a voice message recording subsystem may also be implemented on the mobile device 610. Although voice or audio signal output is preferably accomplished primarily through the speaker 634, the display 622 may also be used to provide an indication of the identity of a calling party, the duration of a voice call, or other voice call related information for example.

[0045] A short-range communications subsystem 640 is a further optional component that may provide for communication between the device 610 and different systems or devices, which need not necessarily be similar devices. For example, the subsystem 640 may include an infrared device and associated circuits and components or a Bluetooth™ communication module to provide for communication with similarly enabled systems and devices.

[0046] It will be appreciated that the above description relates to the preferred embodiment by way of example only. Many variations on the invention will be obvious to those knowledgeable in the field, and such obvious variations are within the scope of the invention as described and claimed, whether or not expressly described.

Claims

1. A method of notifying a first user of an event, comprising the steps of:

setting a first application to notify the first user of the completion of the event as indicated by a second application of a second user;
sending a request to the second application to notify the first application to the completion of the event;
receiving a notification from the second application of the completion of the event; and
sending a reminder to the first user of the completion of the event.

2. The method of claim 1, wherein the event comprises at least one of a location of a second device associated with the second application and a task listed on the second application.

3. The method of claim 2, wherein the second device determines the location using one of the Global Position System, location information received from a station, and the proximity of the second device to a

beacon, and location detection means.

4. The method of claim 3, wherein the reminder is provided to the first user on a first device.
5. The method of claim 4, wherein the reminder is provided to the first device in the form of an email.
6. The method of claim 5, wherein the first application and the second application are calendar or task list applications
7. The method of claim 5, wherein the first device and the second device comprise two-way communication devices.
8. A method of providing a reminder based on the location of a mobile device, comprising the steps of:
 - setting the mobile device to provide a reminder upon the mobile device being within proximity of the location;
 - detecting that the mobile device is within proximity of the location; and
 - providing the reminder on the mobile device.
9. The method of claim 8, wherein the location of the mobile device is detected using one of the Global Position System, location information received from a station, and the proximity of the mobile device to a beacon, and location detection means.

10. The method of claim 9, wherein the reminder is provided to the mobile device in the form of an email.

11. The method of claim 10, wherein the mobile device comprises a two-way communication device.

12. A mobile device for notifying a first user of an event, comprising:

a processing module for setting a first application to notify the first user of the completion of the event as indicated by a second application of a second user
a communication subsystem for sending a request to the second application to notify the first application to the completion of the event and receiving a notification from the second application of the completion of the event; and
a display for displaying a reminder to the first user of the completion of the event

13. The device of claim 12, wherein the event comprises at least one of a location of a second device associated with the second application and a task listed on the second application.

14. The device of claim 13, wherein the second device determines the location using one of the Global Positioning System, location information received from a station, and the proximity of the second device to a beacon, and location detection means. 5
15. The device of claim 14, wherein the reminder is an email.
16. The device of claim 15, wherein the second device 10 comprises a two-way communication device.
17. The device of claim 15, wherein the first application and the second application are calendar or task list applications 15

20

25

30

35

40

45

50

55




Fig. 1

Fig. 2





Fig. 3







Fig. 4

Fig. 5






FIG. 6



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 05 01 7557

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 00/22860 A (DEGNBOL JANUS FRIIS) 20 April 2000 (2000-04-20) * abstract * * page 1, lines 1-13, 22-34 * * page 3, lines 1-27 * * page 5, lines 6-27 * * page 7, lines 14-30 * * page 8, lines 1-5 * * page 11, line 1 - page 12, line 30 * * page 13, lines 7-26 * * page 16, line 23 - page 17, line 18 * -----	1-7, 12-17	H04L29/06 G06F17/60
X	EP 1 008 946 A (LUCENT TECHNOLOGIES INC) 14 June 2000 (2000-06-14) * abstract * * paragraphs [0001], [0003], [0004], [0007], [0009] - [0011] * -----	8-11	
X	WO 01/04577 A (NOKIA NETWORKS OY ; RATSCHUNAS KALEVI (FI)) 18 January 2001 (2001-01-18) * abstract * * page 2, lines 3-20 * -----	8-11	TECHNICAL FIELDS SEARCHED (Int.Cl.7) H04L G06F
A	WO 01/27759 A (12 TECHNOLOGIES INC) 19 April 2001 (2001-04-19) * abstract * * page 2, lines 1-11 * * page 3, lines 1-32 * -----	1-17	
A	US 6 381 580 B1 (LEVINSON RICHARD J) 30 April 2002 (2002-04-30) * abstract * * column 1, line 1 - column 2, line 53 * * column 3, line 60 - column 4, line 56 * * column 13, line 57 - column 15, line 45 * ----- -/--	1-17	
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 13 October 2005	Examiner Lopez Monclus, I.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

 1
EPO FORM 1503 (3.82 (P04C01))



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 05 01 7557

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	US 2002/010615 A1 (JACOBS SIMON) 24 January 2002 (2002-01-24) * abstract * * paragraphs [0002] - [0004], [0009] - [0013] * -----	1-17	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 13 October 2005	Examiner Lopez Monclus, I.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

 1
EPO FORM 1503 (2.82) (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 05 01 7557

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-10-2005

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0022860 A	20-04-2000	AU 6188299 A EP 1151627 A1	01-05-2000 07-11-2001
EP 1008946 A	14-06-2000	CA 2288475 A1 JP 2000199716 A US 6177905 B1	08-06-2000 18-07-2000 23-01-2001
WO 0104577 A	18-01-2001	AU 5839400 A DE 60021191 D1 EP 1200803 A1 JP 2003504744 T	30-01-2001 11-08-2005 02-05-2002 04-02-2003
WO 0127759 A	19-04-2001	AU 1963601 A US 6631363 B1	23-04-2001 07-10-2003
US 6381580 B1	30-04-2002	US 6047260 A	04-04-2000
US 2002010615 A1	24-01-2002	NONE	

EP FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82